



Latitude HD 7' Web SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Reliable internal braking system eliminates need for external shock pack.
- Durable housing and premium webbing increase strength and longevity.
- 360/180° attachment point offers full range of motion.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class

1

Anchor at or above dorsal D-ring

Product shown:
FS-FSP14075-W

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1 (ABOVE D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 29 in. (74 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	not permitted
Min. required fall clearance	5 ft. 11 in. (1.8 m)
For full clearance requirements, see user instructions	

OSHA (BELOW D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 19 in. (48 cm)
Max. free fall distance	36 in. (91 cm)
Use below d-ring	3 ft. (0.91 m)
Min. required fall clearance	8 ft. 1 in. (2.5 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Webbing	25mm UHMPE webbing
Housing	Aluminum
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)



SAFEWAZE

TECHNICAL DATA SHEET

Latitude HD 7' Web SRL-P

LATITUDE

HD

Standards: ANSI Z359.14-2021
OSHA 1910.140 & 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

CONNECTOR

ATTACHMENT

Part Number	Single Leg (S) / Dual Leg (D) / Split Clasp	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	1 Steel Swivel Snap Hook ①	2 Steel Swivel Snap Hook ②	3 Deletic Snap Hook ③	4 Steel Tie Back Hook ④	5 Steel Swivel Rebar Hook ⑤	6 Steel Swivel Rebar Hook ⑥	7 Steel Swivel Rebar Hook ⑦	8 Steel Swivel Rebar Hook ⑧	9 Steel Swivel Rebar Hook ⑨	10 Steel Swivel Rebar Hook ⑩	11 Steel Swivel Rebar Hook ⑪	12 Steel Swivel Rebar Hook ⑫	13 Steel Swivel Rebar Hook ⑬	14 Steel Swivel Rebar Hook ⑭	15 Steel Swivel Rebar Hook ⑮	16 Steel Swivel Rebar Hook ⑯	17 Steel Swivel Rebar Hook ⑰	18 Steel Swivel Rebar Hook ⑱	19 Steel Swivel Rebar Hook ⑲	20 Steel Swivel Rebar Hook ⑳	21 Steel Swivel Rebar Hook ㉑	22 Steel Swivel Rebar Hook ㉒
TH40079-FS007W	1	S	7	UHMPE webbing	1X.05	Aluminum	3.3	X																				
FS-FSP1407-W	1	S	7	UHMPE webbing	1X.05	Aluminum	3.4	X																				
FS-FSP1407-W-RBH	1	S	7	UHMPE webbing	1X.05	Aluminum	4.4																					
FS-FSP1407-W-TBH	1	S	7	UHMPE webbing	1X.05	Aluminum	3.4																					
FS-FSP14075-W	1	D	7	UHMPE webbing	1X.05	Aluminum	6.8	X																				
FS-FSP14085-W-RBH	1	D	7	UHMPE webbing	1X.05	Aluminum	8.8																					
FS-FSP14085-W-GCC	1	D	7	UHMPE webbing	1X.05	Aluminum	8.8																					
FS-FSP15075-W-BWB	1	D	7	UHMPE webbing	1X.05	Aluminum	6.1	X																				
FS-FSP15085-W-BWB	1	D	7	UHMPE webbing	1X.05	Aluminum	8.1																					
FS-FSP14075-W-TBH	1	D	7	UHMPE webbing	1X.05	Aluminum	4.4																					
023-5369	1	D	7	UHMPE webbing	1X.05	Aluminum	5.9	X																				
023-5370	1	D	7	UHMPE webbing	1X.05	Aluminum	7.9																					
FS-FSP1409-W	1	S	9	UHMPE webbing	1X.05	Aluminum	3.6	X																				
FS-FSP1409-W-RBH	1	S	9	UHMPE webbing	1X.05	Aluminum	4.6																					
020-5270	1	S	9	UHMPE webbing	1X.05	Aluminum	3.1																					
FS-FSP1409-W-DL	1	D	9	UHMPE webbing	1X.05	Aluminum	7.2	X																				
FS-FSP1409-W-DL-RBH	1	D	9	UHMPE webbing	1X.05	Aluminum	9.2																					
FS-FSP1409-W-DL-BWB	1	D	9	UHMPE webbing	1X.05	Aluminum	6.5	X																				
FS-FSP1409WDLRBHALU	1	D	9	UHMPE webbing	1X.05	Aluminum	8.5																					
FS-FSP1409WDLRBH-BWB	1	D	9	UHMPE webbing	1X.05	Aluminum	9.3																					
SW8008-10	1	S	10	Steel Cable	Ø3/16	Polymer	5.1	X																				
SW8008-10-ALU	1	S	10	Steel Cable	Ø3/16	Polymer	4.9																					
SW8008-10-RBH	1	S	10	Steel Cable	Ø3/16	Polymer	6.1																					
SW8008-10-ALU-RBH	1	S	10	Steel Cable	Ø3/16	Polymer	5.7																					
SW8008-10-DL	1	D	10	Steel Cable	Ø3/16	Polymer	9.3	X																				
SW8008-10-ALU-DL	1	D	10	Steel Cable	Ø3/16	Polymer	8.9																					
SW8008-10-RBH-DL	1	D	10	Steel Cable	Ø3/16	Polymer	11.3																					
SW8008-10-ALU-RBHD	1	D	10	Steel Cable	Ø3/16	Polymer	10.5																					
FS-FSP1211-G	1	S	11	Steel Cable	Ø3/16	Polymer	6.2																					
FS-FSP1211-SS	1	S	11	S.S Cable	Ø3/16	Polymer	6.2																					
FS-FSP1211-G-RBH	1	S	11	Steel Cable	Ø3/16	Polymer	7.2																					
FS-FSP14095-W	1	D	11	UHMPE webbing	1X.05	Aluminum	8.4	X																				
FS-FSP14095-W-BWB	1	D	11	UHMPE webbing	1X.05	Aluminum	8.4	X																				
FS-FSP14095-W-RBH	1	D	11	UHMPE webbing	1X.05	Aluminum	10.4																					
021-5276	1	S	11	UHMPE webbing	1X.05	Aluminum	4.2																					
021-5286	1	S	11	UHMPE webbing	1X.05	Aluminum	3.7																					
021-5287	1	S	11	UHMPE webbing	1X.05	Aluminum	4.5																					
FS-2011N	1	S	11	UHMPE webbing	1X.05	Aluminum	3.6	X																				
FS-FSP1411-W	1	S	11	UHMPE webbing	1X.05	Aluminum	4.2	X																				
FS-FSP1411-W-RBH	1	S	11	UHMPE webbing	1X.05	Aluminum	5.2																					
FS-FSP1411-W-TBH	1	S	11	UHMPE webbing	1X.05	Aluminum	5.2																					

