



## FS-FSP1420-W

### Northstar Classic 20' Web SRL

\*See chart for additional part numbers, hook configurations, and product weights

#### FEATURES :

- Swivel attachment point offers wide range of motion.
- High strength polymer housing resists impact.
- Heavy duty webbing includes fall indicator.
- Braking system activates quickly to arrest fall.
- All components are Z359.12 compliant.



Class  
**1**  
Anchor at or above  
dorsal D-ring

#### USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

#### STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

#### ANSI CLASS 1 (ABOVE D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 41 in. (104 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	7 ft. 5 in. (2.3 m)
For full clearance requirements, see user instructions	

#### MATERIAL SPECIFICATION

Webbing	25 mm UHMPE webbing
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel

