



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

LVD SAFEWAZE 7' RETRACTIL 018-5026

FICHA TECNICA



CARACTERISTICAS

Las líneas de vida retráctiles Safewaze™ están diseñadas para ser utilizadas como un dispositivo de protección contra caídas para una sola persona. La Serie Web de 7' presenta carcassas de plástico transparente únicas para inspecciones mejoradas de la unidad y un sistema de frenado interno revolucionario, que alivia la necesidad de un paquete de choque externo en una SRL ergonómica tan pequeña. El indicador de caída está cosido en la correa.

DISTANCIA 7 ft (2.13 m)

PESO *(Consulte sobre la configuración requerida)*

MATERIAL Carcasa de plástico de alta resistencia

Cinta de peso molecular ultraalto de 19,5 mm (0,77 pulg.)

Mosquetones de acero forjado o aluminio

Ganchos de refuerzo de acero forjado

Acero forjado detrás del soporte de alma

GANCHO 5,000 lbs (2267.96 kg) Tensile Strength
3,600 lbs (1632 kg) Gate Rated

FUERZA MAXIMA DE DETENCION <1,800 lbs (816.47 kg)

DISTANCIA MAXIMA DE DETENCION Clase A hasta 24 in (60,96 cm) si se usa por encima del anillo en D dorsal Clase B hasta 54 in (137,16 cm) si se usa hasta un máximo de 2 pies por debajo del anillo en D dorsal

CARGA MAXIMA ANSI 130-310 lbs (58.97-140.61 kg)
OSHA up to 420 lbs (190.51 kg)

RESISTENCIA A LA TRACCION 4,200 lbs (1905.09 kg)

STANDAR Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32



TECHNICAL DATA SHEET

safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

7' Web SRD Series Dual Leg Configuration Options

		Web Connection					Housing Connection									
																
DUAL	Length in Feet	Material	1.75" Steel Snaphook	3/4" Aluminum Snaphook	1.75" Steel Form Accommodating Rebar Hook	1.75" Aluminum Rebar Hook	FS-EX313 Dual Bracket	Steel Carabiner	Aluminum Carabiner	9013 Behind the Web Bracket	1014 Behind the Web Bracket	Weight in lbs. including carabiner				
			7	WEB	X				PLASTIC	X	X				5.5	
			7	WEB		X			PLASTIC	X	X				4.7	
			7	WEB			X		PLASTIC	X	X				7.5	
			7	WEB				X	PLASTIC	X	X				6.5	
			7	WEB	X				PLASTIC	X		X			5.3	
			7	WEB		X			PLASTIC	X		X			4.5	
			7	WEB			X		PLASTIC	X		X			7.3	
			7	WEB				X	PLASTIC	X		X			6.3	
			7	WEB	X				PLASTIC				X		4.85	
			7	WEB		X			PLASTIC				X		4.05	
			7	WEB			X		PLASTIC				X		6.85	
			7	WEB				X	PLASTIC				X		5.85	
			7	WEB	X				PLASTIC					X	5.1	
			7	WEB		X			PLASTIC					X	4.3	
			7	WEB			X		PLASTIC					X	7.1	
			7	WEB				X	PLASTIC					X	6.1	
			7	WEB				X	PLASTIC				X		6.85	
			7	WEB				X	PLASTIC					X	7.1	