



Latitude Pro 7' Web SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Reliable internal braking system eliminates need for external shock pack.
- High strength semi-sealed assembly protects internal components from debris to extend product life.
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly.
- 360/180° attachment point offers full range of motion.
- Single leg and dual leg options available.
- Protective label cover for product longevity and traceability.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class

1

Anchor at or above dorsal D-ring

Product shown:
018-5010

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1 (ABOVE D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 27 in. (69 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	not permitted
Min. required fall clearance	5 ft. 9 in. (1.8 m)
For full clearance requirements, see user instructions	

OSHA (BELOW D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 24 in. (61 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	2 ft. (0.6 m)
Min. required fall clearance	7 ft. 6 in. (2.3 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Webbing	20 mm Dyneema® webbing
Housing	Clear resin
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)



SAFEWAZE

TECHNICAL DATA SHEET

Latitude Pro 7' Web SRL-P

LATITUDE

PRO

Standards: ANSI Z359.14-2021
OSHA 1910.140, 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

CONNECTOR										ATTACHMENT																			
Part Number	Single Leg (S) / Dual Leg (D)		Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	Attachment Options																					
	SRL Class							U-Steel Snap Hook ①	U-Steel Sewel Snap Hook ②	Dinetric Snap Hook ③	Steel Tie Back Hook ④	Steel Rebar Hook ⑤	Steel Sewel Rebar Hook ⑥	Steel Sewel Rebar Hook ⑦	Steel Capline Eye Carabiner ⑧	ALU Rebar Hook ⑨	ALU Capline Eye Carabiner ⑩	ALU Sewel Carabiner ⑪	No Attachment	Tip Lock Steel Carabiner ⑫	ALU Capline Eye Carabiner ⑬	ALU Capline Eye Carabiner ⑭	ALU Capline Eye Carabiner ⑮	ALU Snap Hook ⑯	ES-2013 ⑰	Cab Mount Bracket ⑱	Soft Loop ⑲	Integrated BWR ⑳	10-1 BWR ㉑
018-5000	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	2.2	X									X												
018-5001	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	2.0			X							X												
018-5002	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	3.2					X					X												
018-5003	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	2.8							X			X												
018-5004	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	2.8	X										X											
018-5005	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	2.6			X								X											
018-5006	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	3.8					X						X											
018-5007	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	3.4						X					X											
018-5008	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	2.7	X											X										
018-5009	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	2.5			X									X										
018-5010	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	3.7						X						X										
018-5011	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	3.3								X				X										
018-5012	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	2.5	X												X									
018-5013	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	2.3			X										X									
018-5014	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	3.5					X								X									
018-5015	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	3.1							X						X									
018-5016	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	5.4	X											X					X					
018-5017	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	5.0			X									X					X					
018-5018	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	7.4						X						X					X					
018-5019	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	6.6							X					X					X					
018-5020	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	5.2	X												X				X					
018-5021	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	4.8			X										X				X					
018-5022	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	7.2						X							X				X					
018-5023	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	6.4								X					X				X					
018-5024	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	4.8	X																					X
018-5025	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	4.4			X																			X
018-5026	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	6.8						X																X
018-5027	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	6.0								X														X
019-5124	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	4.9	X																					
019-5125	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	4.5			X																	X		
019-5126	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	6.9						X														X		
019-5127	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	6.1								X												X		
020-5269	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	5.9								X													X	
021-5288	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	4.3			X																		X	
023-5366	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	4.7	X																				X	
023-5330	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	6.7						X															X	
023-5367	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	5.9								X													X	
021-5281	1	S	7	Dyneema®Webbing	.7X.05	Clear Resin	2.8					X							X										
018-5037	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	5.2					X																	X
019-5137	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	5.4					X														X			
023-5368	1	D	7	Dyneema®Webbing	.7X.05	Clear Resin	5.2					X																X	

